GEUTEBRÜCK

VIDEO MANAGEMENT

SECURITY MANAGEMENT

VIDEO CONTENT ANALYSIS

INTEGRATION AND MONITORING

SERVICE

HARDWAR

Hardware platform for stationary applications G-ST 8000+



The hardware platform in 19-inch design with higher reliability guarantees optimal interaction with Geutebrück software. Ideal as a stand-alone device for large, demanding systems with very high storage space requirements, as well as for use in networked branches or branch offices.

- Surveillance of larger buildings and company premises.
- Enables the processing of a large amount of data in conjunction with high redundancy requirements.

- High performance model with high reliability due to an integrated RAID system for max. 16 hard disks.
- Possibility to increase the memory space by connecting further external memory systems.
- Depending on the application, the hardware can be configured with appropriate components.
- Higher reliability through the choice of additional redundancy concepts.
- An extended upgrade cycle of the Geutebrück software to 3 years.
- Perfectly adapted to the requirements of video surveillance (CCTV).

Technical data

| Operating System | Windows 2016 Server Essentials for Embedded Systems (64-bit) |
|-----------------------------|--|
| Resolution | 4K |
| Number of slots | 16x HDD, 2x SSD |
| CPU type | 1x XEON |
| GPU Acceleration | Yes |
| Analog extendable | No |
| OS on seperate SSD | Yes |
| RAM | 4 x 4 GB DDR4 ECC SDRAM |
| Storage Interface | SCSI |
| Ethernet | 2 x Ethernet 10/100/1000 base-TX interface |
| USB | 4 x USB 2.0, 4 x USB 3.0 (rear) /1 x USB 3.0 (front) |
| RS-232 | 1 |
| Video outputs | DVI-D, 2x Display Port |
| Audio formats | G.711 (PCM) A-law, µ-law with 8 kHz, Uncompressed PCM up to 16 kHz, AAC |
| Audio outputs | 1 x stereo (line out, phone jack, 3,5 mm) |
| Control inputs | 16 internal floating input contacts, tamper-monitored (switchable) |
| Relay outputs | 8 internal relay outputs, 24 V DC, 1 A |
| Form Factor | 3U |
| Dimension | 482 x 133 x 710 mm (W x H x D) |
| Weight | 24 kg |
| Voltage supply | Redundant power supply unit: 110 - 240 V AC / 60 - 50 Hz \pm 10%, 2 x 760 W (Hot-Swap) |
| Power consumption | Ø 340 W; Max. 410 W |
| Operating Temperature | 0 °C to + 40 °C |
| Certification | CE |
| Warranty period | 3 Years |
| Possible warranty extension | Up to 2 years |
| Order No. | 0.60800 |