

## Weather Proof Housing, big, with splitter G-Case/WPH-1001



- Durable weatherproof housing made of aluminium.
- Concealed cable guide for optimum protection against sabotage of the cable connections.
- Integrated splitter for PoE or PoE+ supply.
- Temperature-controlled windscreen heating to prevent condensation.
- Suitable for wall and ceiling mounting

The weatherproof housing has been specially designed for box cameras. The power supply of the components in the housing is provided by an installed splitter via PoE or PoE+. The housing, made of high-quality, painted aluminium, is particularly suitable for use in climatically harsh outdoor areas. The temperature-controlled heating with heat protection for the lens enables the operation of the built-in devices even at low outside temperatures. and also reliably prevents the windscreen from fogging up. The integrated blower, in turn, ensures that the sensitive electronics of the components in the housing is not overheated. The wall bracket is not included in the scope of delivery.

# Technical data

Protection rating	IP66
Sun shield	Movable sunshield
Heater regulation	yes
Heater supply	12 VDC
Power connection board	yes
Cable access	PG fitting with large passage for field-mounted RJ-45 connector
Concealed access	yes
Weight	4.2 kg (without wall bracket, camera and lens)
Outer dimensions	560 x 194 x 330 (W x D x H, with mounted wall bracket)
Usable internal size	310 x 120 x 85
Material	Aluminium
Cameras	For IP cameras with PoE and w/o PoE
Color	RAL 8022 / RAL 9002 / RAL 1028
Operating Temperature	-40°C - +50°C
Order No.	5.15900