

5 MP Mini-Fixdome Camera G-Cam/EFD-5260



The Fixdome Camera with a resolution of 5 MP and infrared LEDs is suitable for indoor use down to -30°C. Due to its compact design, which can be mounted both on the wall and on the ceiling, it is perfectly protected against sabotage by twisting or violent impacts. The mini version is ideal for inconspicuous installations. The lens including the surrounding infrared LEDs can be panned in one line and thus allows a fixed angle of 45°-90°, suitable for the respective environment.

- Inconspicuous installation in stairwells.
- Non-rotating installation in underground garages.
- Entrance areas.

- This IP camera is suitable for unobtrusive surveillance tasks and allows installation even in dusty or humid environments.

- The integrated infrared LED lighting provides even in absolute darkness sufficient illumination at a distance of up to 15 meters for best image results.

- Wide Dynamic Range to improve the image quality of particularly dark or bright image areas.

- Extended range of functions compared to ONVIF connection due to own G-Core plugin.

Technical data

Mega pixel	5 MP
Effective pixels	2720x1976
Image sensor	1/2.7" Progressive CMOS
Pixel size	2.0 µm
Picture Format	112:81 / 16:9 / 4:3
Lens	f = 2.8 mm
Lens mounting	CS-Mount
Auto Focus	Automatic, Manual, One Touch Function
Auto Back Focus	No
Digital zoom	digital zoom 10x
F-Stop	F2.0
Angle of view	108.3° (H) x 76.5° (V)
Minimum sensitivity	0,08 Lux (color), 0,008 Lux (BW)
Day/Night function	Automatically removable IR-cut filter
IR-LED	850 nm / 15 m
Wide Dynamic Range	HDR Gen3 (130 dB max.)
White balance	Auto, ATW, One Push, Manual
Shutter	1 - 1/10,000 s
Backlight Compensation	No
Text overlay	Yes
Automatic gain control (AGC)	Automatic
Interface	10/100/1000 Mbps Ethernet
OSD Menu	English, German, French, Italian, Korean, Simplified Chinese, Traditional Chinese, Russian, Spanish, Japanese, Portugese
Image rotation	0°, 90°, 180°, 270°
Compression	H.264/H264CCTV, H.265/H265CCTV, MJPEG
Picture rate (full resolution)	H.264/H264CCTV or H.265/H265CCTV with HDR 5M@30fps + 720p@27fps
Video Streaming	Single, Dual, Triple, Quad
Protocols	HTTP, HTTPS, TCP, FTP, RTSP, RTP, UDP, SMTP, SNMP, ICMP, IGMP, DHCP, UPnP, PPPoE, QoS, NTP, DDNS, ARP, IPv4/v6
Network security	User Authentication, IP-Filter, HTTPS (TLS1.2), IEEE802.1X (SHA-2)
ONVIF compatible	Profile S, G, Q, T
Motion detection	4 Zones
Privacy masking	5 adjustable masking zones (8 colors, rectangles, free scalable)
Picture memory	µSD slot (128 GB max.)
Operating Temperature	- 30 °C to + 55 °C
Connectors	RJ-45 für 10/100 Base/T Ethernet; connector for 12 VDC
Voltage supply	PoE IEEE802.3af, class 0, max 5.57 watt DC12V, max 0.54 A
Power Consumption	Approx. 13.7 W @ 12 VDC, 1.14A
Housing	Aluminum/Plastic, near RAL 9003
IP class / vandalism proof	IP 66
Certification	EMC, FCC, CE
Licensing	G-Core
Dimensions mm	Ø105x65 mm
Weight	248g
Optional accessories	5.04742 - G-Cam/EBWM-007 Wall Mount Holder
Application area	Indoor
Brand	Geutebrück
Order No.	5.03748

